

RUNDGEWINDE DIN 405

Gewinde- Nenn Durchmesser	Durchmesser außen mm	Durchmesser Bolzen mm	Durchmesser Kernloch Mutter mm	Steigung mm	Gänge je Inch
Rd 8 x 1/10"	8,254	5,460	5,714	2,540	10
Rd 9 x 1/10"	9,254	6,460	6,714	2,540	10
Rd 10 x 1/10"	10,254	7,460	7,714	2,540	10
Rd 11 x 1/10"	11,254	8,460	8,714	2,540	10
Rd 12 x 1/10"	12,254	9,460	9,714	2,540	10
Rd 14 x 1/8"	14,318	10,825	11,142	3,175	8
Rd 16 x 1/8"	16,318	11,166	12,825	3,175	8
Rd 18 x 1/8"	18,318	14,825	15,142	3,175	8
Rd 20 x 1/8"	20,318	16,825	17,142	3,175	8
Rd 22 x 1/8"	22,318	18,825	19,142	3,175	8
Rd 24 x 1/8"	24,318	20,825	21,142	3,175	8
Rd 28 x 1/8"	28,318	24,825	25,142	3,175	8
Rd 30 x 1/8"	30,318	26,825	27,142	3,175	8
Rd 32 x 1/8"	32,818	28,825	29,142	3,175	8
Rd 34 x 1/8"	34,318	30,825	31,142	3,175	8
Rd 36 x 1/8"	36,318	32,825	33,142	3,175	8
Rd 38 x 1/8"	38,318	34,825	35,142	3,175	8
Rd 40 x 1/6"	40,423	35,767	36,190	4,233	6
Rd 42 x 1/6"	42,423	37,767	38,190	4,233	6
Rd 44 x 1/6"	44,423	39,767	40,190	4,233	6
Rd 46 x 1/6"	46,423	41,767	42,190	4,233	6
Rd 48 x 1/6"	48,423	43,767	44,190	4,233	6
Rd 50 x 1/6"	50,423	45,767	46,190	4,233	6
Rd 52 x 1/6"	52,423	47,767	48,100	4,233	6
Rd 55 x 1/6"	55,423	50,767	51,190	4,233	6
Rd 58 x 1/6"	58,423	53,767	54,190	4,233	6
Rd 60 x 1/6"	60,423	55,767	56,190	4,233	6
Rd 62 x 1/6"	62,423	57,767	58,190	4,233	6
Rd 65 x 1/6"	65,423	60,767	61,190	4,233	6
Rd 68 x 1/6"	68,423	63,767	64,190	4,233	6
Rd 70 x 1/6"	70,423	65,767	66,190	4,233	6
Rd 72 x 1/6"	72,423	67,767	68,190	4,233	6
Rd 75 x 1/6"	75,423	70,767	71,190	4,233	6
Rd 78 x 1/6"	78,423	73,767	74,190	4,233	6
Rd 80 x 1/6"	80,42	75,767	76,190	4,233	6

